




Sface900



Face Fingerprint RFID Access

MULTI-BIOMETRIC TIME ATTENDANCE & ACCESS CONTROL SYSTEM

Face capacity : 1200(1:N), 3000(1:1)
 Fingerprint capacity: 2000 (Optional 4000)
 ID Card capacity: 10,000
 Logs Capacity: 100,000
 Display: 4.3-Inch Capacitive Touch Screen
 Communication : TCP/IP, RS232/485, USB Host
 Fingerprint Sensor : 500 DPI Optical sensor
 FAR : $\leq 0.0001\%$ FRR : $\leq 1\%$
 Identification speed : < 0.5 sec
 Push Data: Yes
 Wiegand Signal : Output
 Power supply: 12V 3A
 Operating Temperature; 0°C to 45°C
 Operating Humidity: 20% - 80%
 Dimensions: 195.5 x 166.5 x 120mm(L x W x T)
 Package Weight: 1.6kg

Compatible Software & SDK

SmartOffice
Time and Attendance Software

- Smart office suite desktop and web
- Smart office 365 cloud
- SDK for desktop applications

Optional

Battery : 7.4 V, 2000 mAh Backup Battery,
Mifare Card, Wi-Fi, 3G GPRS

Compatibility

- Compatible with Multi Door controllers via weigand
- External Speaker output available (optional)
- External Bulb Output available (optional)
- Support External Printer

Features

- High Verification speed
- Standard Functions : Automatic Status Switch, Self-Service Query, Work Code, SMS,DST, T9 Input, 9 Digit User ID, Scheduled Bell,
- Photo ID Interfaces for : 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo , enhancing the security level of verification
- Outside installation (maximum 12,000 lux)