



D2180S

⇒ 18 Zones Standard: WALK THROUGH METAL DETECTOR

Power Supply: AC85 V - 264 V

Working Temperature : -20°C to +50°C Working Frequency : 4KHZ—8KHZ

Standard Internal size: 2000mm(H)x700mm(W)x

605mm(Deep)

Standard External size: 2230mm(H)x830mm(W)x

730mm(Deep)

Package size for door panels: 2260x650x260mmx1ctn
Package size for control unit: 780x390x250mmx1ctn

Gross weight: 70KG

Features:

- Eighteen mutual over-lapping detecting zones,
 Simultaneous alarm from multi-Zones
- Small LCD screen, English operating software, easy to operate
- Sensitivity adjustable: Each zone has 256 sensitivity level, 0-255 adjustable
- ➤ Sound & LED alarm: Both Side LED indicator, easily show where the metal is
- ➤ Automatically count passengers and alarm times
- > Alarm strength indicator on control panel

- Password protection, only the authorized person can operate
- Easy assembly: designed with only 2 pieces cables and 8 screws, simply-to-follow instruction
- Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc
- Using high density fireproof material
- Program Self-diagnostic when power on, no need initial or periodic calibration
- Modularization design, easy for maintenance and replacement
- 4-8 hours backup battery(Option)