



SA521

➔ Standalone Access Control

Operating voltage : DC 12V₋+ 10%
 User Capacity : 2000
 Card Reading Distance : 3-6 cm
 Standby Current : <60mA
 Output load Lock : 25₋+ 5 mA
 Lock Output Load : Max 3A
 Alarm Output Load Max : 20A
 Operating Temperature : -45°C ~ 60°C
 Operation Humidity : 10% - 90% RH
 Waterproof : Conforms to IP68
 Adjustable Door Relay time : 0 -99 seconds
 Adjustable Alarm Time : 0- 3 minutes
 Wiegand Interface : Wiegand 26 bit
 Wiring Connections : Electric Lock,
 Exit Button, External Alarm, External reader

Features:

- Waterproof, conforms to IP68
- Strong Zinc Alloy Electroplated anti-vandal case
- Full programming from the keypad
- 2000 uses, supports Card, PIN, Card + PIN
- Can be used as a stand alone Keypad
- Backlight keys
- Wiegand 26 input for connection to external reader
- Wiegand 26 output for connection to a controller
- Adjustable Door Output time, Alarm time, Door Open time
- Very low power consumption (30mA)
- Fast operating speed, <20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Built in light dependent resistor (LDR) for anti tamper
- Built in buzzer
- Red, Yellow and Green LEDS display the working status