

inBio 260



➔ Multidoor Access Control - 2 Door

CPU : 32 bit 400MHz CPU

RAM : 32M

Flash Memory : 128M

Fingerprint Capacity : 3,000

Card holders Capacity : 30,000

Log Events Capacity : 100,000

Communication : TCP/IP and RS-485

Power : 9.6V-14.4V DC

Numbers of readers supported : 8(4 RS-485 Reader,
4 26-bit wiegand reader)

Types of readers supported : 26-bit Wiegand and
RS485 FR Series Reader

Number of Inputs : 6(2 Exit Device, 2 Door Status, 2 AUX)

Number of Outputs : 4 (2-Form C Relay for
Lock and 2-Form C Relay for Aux Output)

Package Dimension : 350(L)×90(H)×300(W)mm

Package Weight : 3.6kg

Operating Temp : 0 - 45 °C

Operating Humidity : 20% to 80%

Software and Database Supported :

Access Security System 3.5 (Desktop Version)

Database Type:- MS Access / MS SQL

Features:

- Embedded Fingerprint verification and advance access control function
- It can be installed easily on your network also support TCP/IP and RS485 communication
- 1/2/4 Door models can be mixed and matched in an optimised System Architecture
- Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- Anti-Passback, Interlock, First-Card Opening, Multi-Card Opening
- Duress Password Entry, and Auxiliary input/output linkages are inbuilt into controller firmware