



F22

## ⇒ F22 - Ultra Thin Fingerprint Time Attendance & Access Control System

Display: 2.4-inch TFT LCD Color Screen

Fingerprint Capacity: 3000

Card Capacity: 5000

Transaction Capacity: 30,000

Sensor: SilkID Sensor

Communication: RS232/485, TCP/IP,

USB-host, Wi-Fi

Access Control Interface: 3rd Party Electric Lock,

Door Sensor, Exit Button, Alarm

Wiegand Signal: Input, Output

Aux. Input: lea for linkage function

Functions: DST, Automatic Status Switch,

Record query, T9 input, 14 digit user ID,

Anti-passback, Scheduled-Bell, Printer(Optional),

Power Supply: 12V DC,3A

Operating Temperature : 0 °C- 45 °C

Operating Humidity: 20%-80%

Dimension(LxWxH): 158.5x78.0x19.4mm

## Function

- 2.4-inch TFT color screen and Touch keys
- Ultra thin and elegant design
- Full Access Control Features: Anti-passback,
  access control interface for 3rd party electric lock,
  door sensor, exit button, alarm
- Standard Wi-Fi
- Network interface by TCP/IP or RS485
- Built-in auxiliary input with enhanced flexibility to link with wired detector or emergency switch
- Multiple Verification Modes: Multi-verification methods (card is optional) providing user various choices

