



## Canteen Management System

### ➔ P160 with Printer (Serial Port Thermal Printer)

Display : 2.8-inch TFT Color Display  
Palm Capacity : 600 (Standard)  
Fingerprint Capacity : 3,000  
ID Card Capacity : 10,000 (Optional)  
Logs Capacity : 100,000  
Communication : TCP/IP, USB-Host  
Standard Functions : Automatic Status Switch,  
Self-Service Query, Work Code, T9 Input,  
9 Digit User, ID, DST, Scheduled-bell, SMS,  
RS232 Printer ; AC module 1: Exit Button, Door Lock,  
Alarm, 12V OUT, AUX IN  
Optional Function : ID Card, MIFARE Card  
AC module 2: Exit Button, Door Lock, Alarm,  
12V OUT, AUX IN, Door Sensor, RS485,  
Wiegand IN/OUT.  
Power Supply : 12V 1.5A  
Verification Speed : ≤1 sec  
Operating Temperature : 0 - 45 °C  
Operating Humidity : 20% - 80%  
Dimensions : 179.95 x 134.94 x 38.5 mm

### Features

Visitors Record  
In & Out attendance  
Breakfast, Lunch, Dinner attendance Reports  
Meal Planning Reports i.e. Breakfast, Lunch, Dinner  
Supports Serial Port Thermal Printer