



SPEEDFACE - 5 SE



Face



Touch
Screen



Masked
Face



Live Body
Detection



RFID
Mifare



WiFi



TCP/IP



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	3000
Card Capacity	3000
Max User	3000
Log Capacity	50,000

Features

5-inch capacitive touch screen

High-End CPU-DualCoreARM Cortex-A7@900 MHz

Remotely Firmware Upgradation.

Detect 5 person at a time

5-inch IPS display all-sight LCD touch screen with 480*854 resolution.

IP54 Grade Highly finished slim device.

Highly reliable and durable

Recognition speed 0.5 seconds



SpeedFace - 5 SE

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.1%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Verification time	<=1 second
RF card options	Mifare

Audio/Visual

LCD	5.0" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Access control

Wiegand out	YES
Relay	YES
Live Detection	YES
Storage	512MB RAM, 4GB ROM

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	185.80 ± 0.50 x 93.78 ± 0.50 mm
	0.30 X 22.50 ± 0.50 mm



Auto Focus



Autofill light



Long Distance Verification



Accepts 5 people at a time

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control