

RP3200 Plus

3" Thermal Receipt Printer



Specification:

Parameter	RP 3200 Plus
Print method	Direct thermal line printing
Resolution	203 DPI
Print width	Max 72mm
Print speed	Max 200 mm/sec
Memory	4 MB Flash
sensor	Paper end & cover open
Cash drawer control	1 cash drawer
Interface	USB+Serial+Ethernet
Barcodes	JAN8 (EAN8), JAN13 (EAN13), ITFUPC-A, UPC-E, CODE 39, CODE 93, CODE 128, CODABAR, PDF 417
Character set	USA, France, Germany, UK, Denmark I, Denmark II, Italy, Sweden, Spain I, Spain II, Japan, Norway, Latin America, Korea, Japanese, Chinese, GB18030, Gb2312
Fonts	Font A(12*24), Font B(9*17), Kanji Font(24*24)
Paper Type	Continuous Paper, Marked Paper
Paper thickness	0.06mm-0.08mm
Paper roll width	80±0.5mm
Paper cut	Full cut, partial cut, tear off
Input	AC 100-240 V, 50/60Hz
Output	24V, 2.5A
Print Head Life time	100km
Cutter life time	1,000,000 cuts
Operation condition	5~45deg Celcius, 20~90% RH (40 deg Celcius)
Storage condition	~-40deg Celcius - 60deg Celcius 20%~93%RH (40deg Celcius)
Dimension	126(W)*160.5(L)*116.5(H)mm