



N-Access 10 Pro



Finger



RFID





USB



Access Control

Fingerprint Access Control System

Storage Capacity

Finger Capacity	3000
Card Capacity	1000
Max User	1000
Password	1000
Log Capacity	1,00,000



Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

Output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

N-Access 10 Pro

Communication Interface

Communication	USB
---------------	-----

Biometric

FAR	0.0001%
FRR	0.01%
CPU	High speed industrial grade CPU
Verification time	<=0.5 second
RF card options	125kHz EM (Standard)

Audio/Visual

LCD	2.4" TFT Color Display
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand output	YES
Relay	YES, One Realy

Power & Enviroment

Operating Temperature	0°C ~ 45°C
Power	12V DC / 2A
Dimension	100.24 x 105.2 x 29.4 mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



USB



Unaffected by High Temperatures 0° ~ 45°



Time Attendance



Access Control



SSR Report
(Self-Service-Recorder)

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control