



ONETOUCH 16PORT POE SWITCH – OT 1716P

Overview

Onetouch 16 port 10/100M Rackmount Unmanaged PoE Switch provides the seamless network connection. It has 16*10/100M PoE ports + 2*1000M RJ45 Ports + 1*100/1000M SFP Ports PoE Switch, Port 1-16 can support IEEE 802.3af/at standard PoE power supply, single port PoE power up to 30W, and the maximum POE output power is 200W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP, visual intelligent building intercom through network cable, and meet the network environment that needs high-density PoE power supply

Feature

16*10/100M + 2*10/100/1000M RJ45 uplink + 1 *100/1000M SFP uplink PoE Switch,
 1*16 ports support IEEE802.3af/at
 Comply with IEEE 802.3, IEEE 802.3u , IEEE 802.3ab standards
 Power Wattage is 200W ,PoE port support AF/AT intelligent recognition.
 Standard power is 12.5W/port, Maximum power: 30W/port
 Support Port self-healing, VLAN, extend 250 meter distance
 Auto Speed Change, Priority port
 With the Dial code switch, support port priority by default.
 E: AI Extend 250 meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 10M/100M within 100 meters
 V: Turn on, 1-24 Port support each port Isolation & VLAN;
 D: Turn on, 1-24 Port support AI-PoE Network self-healing mode
 PoE Watchdog function - Automatic solve the device problem
 Supports POE devices such as wireless access points (APs) and network surveillance cameras through Category 5/6 Ethernet cables;

CE . EMC . FCC Certified

FEATURES

- 16 X 10/100/1000 Mbps PoE +2*10/100/1000M RJ 45 Uplink+1 Sfp Uplink
- Fully IEEE802.3af/at Standard
- Surge Protection Upto 6Kva
- PoE Power Budget –200W
- Interface: RJ45 10/100 Mbps
- Processing 802.3x Full Duplex
- Bandwidth 9.2 Gbps (non-blocking)
- Network Latency less then 20ms
- Power Input : 230 V AC /52V DC
- Operating Temp: -10 to 55 C
- Humidity: 90%

Ordering Information
 Model : OT-1716P
 2 Year Warranty

To Re-engineer , Re-invent and Realize your networking plans email to

channelsales@discreet.co.in