




Visible Light Indoor Facial Recognition

Storage Capacity

Face Capacity	1,500	
Palm Capacity	500	
Finger Capacity	5,000	
Mifare Card Capacity	1,500	
Max. User	1,500	
Log Capacity	2,00,000	

Features

- Speedy recognition to avoid long queue
- Dual camera for live body sensing & observation
- Feather touch keypad for intuitive operation
- Slim access control to secure your premises
- Multiple authentication modes like Face, Palm & Fingerprint



N-F22

"N-F22 tops the list in matter of style and decency it adds to your place."

Communication Interface

Communication

Wi-Fi, TCP/IP, USB

Biometric

Yes
500 DPI
0.01%
0.001%
Linux
<=1 second
13.56MHz Mifare

Audio/Visual


Keypad	Feather Touch Keypad
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand In & Out	Yes
Relay	Yes
Anti Passback	Yes
Access Control Function	Auxilury Input,
	Multi-identification mode
Exit Reader	N-FR12, Wiegand Reader,
	Push Button, No Touch , Bell

Power & Enviroment

Operating Temperature	0°c ~ 45°c
Power	DC 12V / 2A
Dimension	185 x 72 x 25 mm





Long Distance Verification



1 meter

Unaffected by High Temperatures 0° ~ 45°

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Connect with us on

ſ	BiomaxOfficial	۲	BioMax Security
0	biomaxsecurity	in	BioMax Access Contro

Certified by () C E FC

www.biomaxsecurity.com