

NCS-5CF

Flushmount Chairman Unit



OVERVIEW

NCS-5CF is a flush mount type discussion microphone unit designed as a chairman unit for Novo Conference System. The microphone unit is engineered in high-quality copper zinc die cast housing. The microphone connects to the NCS-110CU central control unit via network category 5/6 cable. The unit comes with a screw type detachable microphone port to connect the gooseneck microphone in it. The chairman unit prioritizes it self over all other delegate units via override button



TECHNICAL SPECIFICATIONS

Polar pattern	Cardioid Condenser
Frequency response	50Hz-20KHz
Sensitivity	-20dBV (+/-3dB) (0db=1Vpa, f=1KHz)
Maximum input sound pressure level	110dB (THD < 5%, f=1KHz)
Signal to noise ratio (A-weighted)	> 100dBA (THD<1%, f=1 KHz)
Distortion	<0.1%
Power supply	24V DC (supplied by the controller)
Power consumption	0.72W
Unit interface	RJ45 network input
Weight	about 345g (without microphone)
Dimension (mm)	100 (L) x 42 (W) x 90(D)

KEY FEATURES

- Recessed enclosure design for discreet looks
- High Quality Copper Zinc alloy die-cast body
- Detachable Screw Type Gooseneck Microphone
- Backlit Speak & Override button