

NCS-5DF

Flushmount Delegate Unit

OVERVIEW

NCS-5DF is a flush mount type discussion microphone unit designed as a delegate unit for Novo Conference System. The microphone unit is engineered in high-quality copper zinc alloy die cast housing. The microphone connects to the NCS-110CU central control unit via network category 5/6 cable. The unit comes with a screw type detachable microphone port to connect the gooseneck microphone in it. The delegate unit has a mute button to control its integrated microphone



TECHNICAL SPECIFICATIONS

Polar pattern	Cardioid Condenser
Frequency response	50Hz-20KHz
Sensitivity	-20dBV (+/-3dB) (0db=1Vpa, f=1KHz)
Maximum input sound pressure level	110dB (THD < 5%, f=1KHz)
Signal to noise ratio (A-weighted)	> 100dBA (THD<1%, f=1 KHz)
Distortion	<0.1%
Power supply	24V DC (supplied by the controller)
Power consumption	0.72W
Unit interface	RJ45 network input
Weight	about 345g (without microphone)
Dimension (mm)90(D)	100 (L) x 42 (W) x 90(D)

KEY FEATURES

- Recessed enclosure design for discreet looks
- High Quality Copper Zinc alloy die-cast body
- Detachable Screw Type Gooseneck Microphone
- Backlit Speak & button