



Face & Fingerprint Access Control

Storage Capacity

Face capacity	500	
Finger Capacity	1,500	
Card Capacity	500	
Max User	500	
Password	500	
Log Capacity	1,00,000	

Features

High-Speed and Accurate Face Identification Good adaptation for dry, moist and rough fingerprints. Face, Fingerprint, Card, Password & Authentication Supremely low Electric energy consumption. Highly reliable and durable.



N-BM300 Pro

"Empowering Security, Redefining Access: Elevating Features to Meet Your Demands."

N-BM300 Pro

Communication Interface

Communication	USB		Accepts moist and rough Finger
Biometric			
Verification time	<=0.5 second		Accepts Color & Mahendi Finger
Sensor type	500 DPI		
Audio/Visual		Ϋ́́,	USB
LCD			
	2.4" TFT Color Display	0-	
Use Environment	Indoor		Unaffected by High Temperatures 0°C ~ 50°C
Language	English		

Access control

Weigand In & Out	Yes
Auxiliary (Fire)	Yes (Input)
Support	KR500M, Push Button, Bell

Power & Enviroment

Operating Temperature	0°C ~ 50°C
Power	DC 12V / 2A
Dimension	100.24 x 105.2 x 29.4 mm



Access Control



SSR Report (Self-Service-Recorder)

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on

(f) BiomaxOfficial BioMax Security

biomaxsecurity

(in) BioMax Access Control

