

Multibio – 300

Visible Light Facial Recognition



Face



RFID



Wi-Fi



TCP/IP



Access
Control

Visible Light Indoor Facial Recognition

Storage Capacity

Face Capacity	1,500
Palm Capacity	500
Card Capacity	2,000
Password Capacity	2,000
Log Capacity	2,00,000
Max User	2,000

Features

Speedy recognition to avoid long queue

Large display with easy handling features

Dual camera for live body sensing & observation

Camera support low light and normal light

Auto ON/OFF Energy saving light

Access control to secure your premises

Multiple authentication modes like Face, Palm & Card



Multibio – 300

Communication Interface

Communication	Wi-Fi, TCP/IP, USB
---------------	--------------------

Biometric

OS	Linux
Recognition distance	0.5-1 meters
Fingerprint Sensor	500 DPI Optical Sensor
FAR	0.00001%
FRR	0.001%
RF Card Options	125 kHz Proxy

Audio/Visual

LCD Display	4.3" IPS Display
Keypads	Feather Touch
Camera	2 MP Binocular camera
Voice instruction	16-Bit Hi-Fi Voice
Resolution	480*272 Pixel

Access Control

Relay	Yes
Exit Reader	Push Button, No Touch

Power & Enviroment

Operating Temperature	Indoor 0°C - 45°C
Power	DC 12V / 2A
Dimension	125 x 139 x 28.4 mm
Working Humidity	10% - 90%



Auto Focus



low light Verification



Long Distance Verification

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control