BioMax®

Multibio – 500

Visible Light Facial & Fingerprint Recognition

Face	Finger	RFID	Wi-Fi	TCP/IP	Access Control

Visible Light Indoor Facial Recognition

Storage Capacity

Face Capacity	1,500
Finger Capacity	5,000
Palm Capacity	500
Card Capacity	2,000
Log Capacity	2,00,000
Max User	2,000

Features

Speedy recognition to avoid long queue

Large display with easy handling features

Dual camera for live body sensing & observation

Camera support low light and normal light

Auto ON/OFF Energy saving light

Access control to secure your premises

Multiple authentication modes like Face, Palm, Fingerprint & Card

Multibio – 500

Communication Interface

Communication	Wi-Fi, TCP/IP, USB

Biometric

OS	Linux
Recognition distance	0.5-1 meters
Fingerprint Sensor	500 DPI Optical Sensor
FAR	0.00001%
FRR	0.001%
RF Card Options	125 kHz Proxy

Audio/Visual

LCD Display	4.3" IPS Capacitive
	touch screen
Camera	2 MP Binocular camera
Voice instruction	16-Bit Hi-Fi Voice
Resolution	480*272 Pixel

Access Control

Relay	Yes
Exit Reader	Push Button, No Touch

Power & Enviroment

Operating Temperature	Indoor 0°C - 45°C
Power	DC 12V / 2A
Dimension	125 x 139 x 28.4 mm
Working Humidity	10% - 90%

Auto Focus

low light Verification

1 meter

Long Distance Verification

Software

Desktop, Web, Cloud

Time Attendance

Access Control

Employee Self Service

Mobile App

Connect with us on

BiomaxOfficial   BioMax Security

biomaxsecurity   BioMax Access Control

www.biomaxsecurity.com