

Best Product in **Indian** Market

**MADE IN INDIA**  
**ZERO % REJECTION**

**4GB RAM + 64GB ROM with 7 inch Screen**


**T502 L1**



C Type



Bluetooth



DC Charging



USB Link

IS 13252(Part 1):2010



BIS Approved Product



**T502 L1**



TCP/IP



4G/5G



WiFi



GPS



Safety Net Pass

**FM220U L1 Scanner Inside**

**AADHAAR ENABLE BIOMETRIC**

CONFIGURATION :

|              |                   |                                      |
|--------------|-------------------|--------------------------------------|
| Product Form | Product Form      | AADHAAR ENABLE BIOMETRICS ATTENDANCE |
|              | Connectivity      | LAN, USB, WI-FI, BT, 2G, 3G, 4G LTE  |
|              | Casing Type       | Polycarbonate                        |
| LCD          | Screen Size       | 7 Inch                               |
|              | Screen Resolution | 1280 x 800 IPS Touch Screen          |
| TP           | Touch Module      | 5 Points Multi-Touch G+G             |
| Battery      | Type              | Lithium-ion 14650                    |
|              | Capacity          | 3.7V/4000mAh                         |
|              | Endurance         | 2 - 4 hours                          |
| USB          | USB Type          | C Type                               |

HARDWARE :

|           |          |                              |
|-----------|----------|------------------------------|
| CPU       | Speed    | Quad Core 1.6 Ghz            |
| GPU       | Type     | IMG 8XE 1PPC@570M            |
| RAM       | Capacity | 4GB DDR3                     |
| ROM Flash | Capacity | 64GB                         |
| Camera    | Front    | 5MP                          |
| Speaker   | Built In | Built-in 8Ω/0.8W speaker * 1 |
| G_Sensor  | Built In | 3 axis accelerometer         |

NETWORK :

|           |             |                                          |
|-----------|-------------|------------------------------------------|
| WIFI      | WiFi Module | WIFI 802.11 ac/b/g/n 2.4G+5G             |
| Bluetooth | BT Module   | BT 5.0                                   |
| 2G GSM    | Built In    | 850 900 1800 1900                        |
| 3G UMTS   | Built In    | 900 2100                                 |
| 4G LTE    | Built In    | B1 B3 B5 B7 B8 B28A B28B B38 B39 B40 B41 |

*Realtime T502 L1*  
*(Aadhaar Enable Biometrics Attendance Device)*

INTERFACE :

|                    |                                             |                                                                                                                                                                                      |
|--------------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Memory Card Socket | External Memory                             | Support 16GB/32GB/64GB/128GB                                                                                                                                                         |
| SIM Card Slot      | Internet Data                               | 1 & 2 SIM Card                                                                                                                                                                       |
| USB Interface      | USB Interface Type A                        | 1 port                                                                                                                                                                               |
|                    |                                             |                                                                                                                                                                                      |
| LAN                | Support                                     | RJ 45                                                                                                                                                                                |
| Fingerprint        | STQC CERTIFIED<br>Single Finger Scanner     | Prism and Lens should be intrigrate part of the optics of the FP scanner, to prevent spoofing by removing prism and directly using printed Fingerprint image instead of Live Finger. |
|                    | Sensors                                     | CMOS sensor                                                                                                                                                                          |
|                    | Scanning                                    | 1/15 second                                                                                                                                                                          |
|                    | Image resolution                            | 500 dpi (H),500 dpi(V)                                                                                                                                                               |
|                    | Image capture format                        | 13.3 x 16.4(mm) (H * V)                                                                                                                                                              |
|                    | Scanner output image size                   | 264 * 324 pixels(H * V)                                                                                                                                                              |
|                    | Gray Level                                  | 8bits/pixel,max 256 gray scales                                                                                                                                                      |
|                    | Image ratio of length to width              | 01:01                                                                                                                                                                                |
|                    | Scanner interface cable                     | Standard USB compliant cable                                                                                                                                                         |
|                    | Power supply                                | 1 watt approx(from USB port)(200mA,approx,standby:60mA)                                                                                                                              |
|                    | Minimum hardware                            | P3 800MHz CPU or up,256MB,USB2.0                                                                                                                                                     |
|                    | Distortion                                  | <1%                                                                                                                                                                                  |
|                    | Temperature<br>(without external enclosure) | 0°C~50°C                                                                                                                                                                             |
|                    | Humidity                                    | <90% non condensing                                                                                                                                                                  |
|                    | Scanning light source                       | infrared red (940nm)                                                                                                                                                                 |
|                    | Operating volts                             | +5V Tolerance 5% (USB connector)                                                                                                                                                     |
|                    | Scanner                                     | Optical                                                                                                                                                                              |
| DC Jack            | Input Device                                | Support                                                                                                                                                                              |

ACCESSORIES :

|                   |                        |                                     |
|-------------------|------------------------|-------------------------------------|
| Power Adapter     | Standard Configuration | DC Jack ( 5volt 3 amp) Fast Charger |
| Type-C Patch Cord | Standard Configuration | Yes                                 |

SOFTWARE :

|                  |                                                            |                                          |
|------------------|------------------------------------------------------------|------------------------------------------|
| Operating System | Operating System Version                                   | Android 11.0                             |
|                  | SafetyNet passed, un-rooted and RD services (UIDAI) tested |                                          |
|                  | GMS                                                        | Direct Contract between Google and Brand |