

CP-URP-H75EN-4K

75" 4K Ultra HD Interactive Display

- Android Operating System
- 4K DLED display with Zero Air Gap technology that delivers a clear image in sharp, vivid colors
- Wireless screen sharing from multiple devices with an intuitive, easy-to-use system
- Ultra-smooth writing experience with handwriting recognition
- Quick file sharing by scanning a QR code, with easy file encryption for added privacy and security
- Optional OPS module, dual-system switchable.



About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-URP-H75EN-4K

75" 4K Ultra HD Interactive Display

Feature	Specification
Display Size	75 inch (190.5 Cm.)
CPU	Quad-core A55
Operating System	Android 11
Writing Mode	Finger + Pen
RAM & ROM	4GB & 32GB
Aspect Ratio	16:9
Contrast Ratio	1200:1
Backlight	DLED
Brightness	400 cd/m ²
Resolution	3840 (H) × 2160 (V)
LCD Response Time	8 ms (typ.)
Viewing Angle	178°(H)/178°(V)
Refresh Rate	60 Hz
Lifespan	50,000 hours
Wi-Fi	Wi-Fi 5, 2.4 GHz/5 GHz; Integrated Wi-Fi 802.11 b/g/n/ac, supports PEAP/EAP-GTC authentication protocol within 802.lx
Wireless Access Point	Wi-Fi 5, 2.4 GHz/5 GHz; Supports enabling Hotspot and Wi-Fi at the same time
IR Receiver	Support
Touch Technology Type	Infrared Touch Technology
Touch Points	Android: 32, Windows: 40
Touch Accuracy	± 1 mm (over 90% Area)
Touch Height	<2.5 mm
Touch Response Time	<10 ms
Valid Touch	2 mm
Color Depth	1.07B (10 bits)
IrDA	1

Feature	Specification
Communication Mode	USB
Built-in Speaker	2
Power	2.0 sound channel, front-end: 2 × 15 W
Button	8 buttons (power, home, menu, signal source, touch lock, curtain, volume, and annotation)
Anti-light Interference	Anti-dazzle tempered glass
Surface Hardness	8H
Light Sensor	1 (for auto brightness adjustment)
Bluetooth	Bluetooth 5.2
Front Ports	Type C × 1 (4K@60 Hz, Touch); HDMI In × 1 (4K@60 Hz); USB 3.0 Type-B × 1 (Touch); USB 3.0 Type A × 2; Mic In × 1 (3.5 mm port)
Rear Port	Type C × 1 (4K@60 Hz, Touch); HDMI In × 2 (4K@60 Hz); VGA In × 1 (1080p@60 Hz); USB 3.0 Type-B × 3 (Touch); HDMI Out × 1; USB 3.0 Type A × 2; Micro USB × 1; RS-232 × 1; RJ45 In × 1; RJ45 Out × 1; Audio In × 1 (3.5 mm port, used to play sound with VGA); Audio Out × 1 (3.5 mm port); SPDIF Out × 1 (Optical port); OPS slot × 1
Glass	4 mm Anti-dazzle tempered glass
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Temperature	-10 °C to +50 °C (+14 °F to +122 °F)
Operating Humidity	10%–90% (RH)
Storage Humidity	10%–90% (RH)
Power Supply	100– 240 VAC, 50/60 Hz
Power Consumption	150 W (typ.); 300 W (max.)
Standby Power Consumption	0.5 W
Installation	Wall mount; floor-standing
Casing	Metal
Dimensions	1,707.5 mm × 93.0 mm × 1,050.0 mm (67.22" × 3.66" × 41.34")
Weight	52 kg

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com

