

AJAX



A New Generation
Of Wireless Security Systems



We build a security system from scratch

Using our passion for combining art with technology, we created a super-reliable, elegant, easy-to-install and user friendly security system



About AJAX

Driving innovation in security

Ajax systems was founded in 2011 by alexander konotopskyi. Now the company already employs over 300 people. The product is designed and manufactured in ukraine. In 2015 ajax systems company received 1 million usd from the international venture capital fund smrk to scale on international markets.

The new generation of wireless security systems

Ajax is a new generation of wireless security systems with elements of a smart home. The ajax starterkit has everything necessary to protect your premises: hub (the brain of the

system), a motion detector, a door opening detector, a keyfob. You can choose to add other detectors and gadgets available in the ajax ecosystem to your starterkit to enlarge, and enhance your protection. Due to the distinctive design and solutions in two colors (black/white), these devices will look stylish even in designer interiors.

New Ajax devices

The Ajax family of devices has grown to include a wall-mounted keyboard, a miniature home siren, and two new advanced models of current Ajax detectors.

- Ajax keypad
- Ajax home siren
- Ajax fire protect plus
- Ajax door protect plus
- Ajax security system



1 Combined Motion & Glass Break Detector | CombiProtect (8IN)

CATEGORY



Classification	: Electro-optical combined radio channel security detector
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	: PIR sensor, electret microphone
Alarm signal delivery time	: 0,15 s
Motion detection distance	: Up to 12 m
Detection angles	: Horizontal — 88.5° Vertical — 80°
Recommended installation height	: 2,4 m
Break detection distance	: Up to 9 m
Detection angle	: 180°
Sensitivity	: Adjustable, 3 levels
Power supply	: Battery: CR123A battery Power supply voltage: 3 V Battery life — up to 5Yr
Jeweller radio technology	: Communication range with central unit — up to 1,200 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: 110x65x50 mm Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

2 Magnetic Opening | DoorProtect (8IN) Detector

CATEGORY



Classification	: Point magnetic and contact radio channel security detector
Installation method	: Indoors
Compatibility	: Operates with all Ajax hubs, range extenders, ocBridge Plus, uartBridge
Sensing element	: Reed switch
Alarm signal delivery time	: 0,15 s
Activation threshold	: Small magnet — 1 cm Big magnet — 2 cm
Power supply	: Battery: CR123A battery Power supply voltage: 3V Battery life — up to 7 years
Jeweller radio technology	: Communication range with central unit — up to 1,200 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

3 Magnetic Opening | DoorProtectPlus (8IN) Detector

CATEGORY



Classification	: Combined point magnetic contact and vibration radio channel security detector
Installation method	: Indoors
Compatibility	: Operates with all Ajax hubs, and range extenders
Sensing element	: Reed switch, accelerometer
Alarm signal delivery time	: 0,15 s
Activation threshold	: Small magnet — 1 cm Big magnet — 2 cm Tilt: more than 5°
Power supply	: Battery: CR123 A battery Power supply voltage: 3V Battery life — up to 5 years
Jeweller radio technology	: Communication range with central unit — up to 1,200 m in an open space Two-way communication between devices Operating frequencies — 865-867 MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

4 Wireless Touch | Keypad (8IN) Keyboard

CATEGORY



Color	: Black/white
Device type	: Wireless
Use	: Indoor
Keyboard type	: Sensor
Number of buttons	: 15
Duress code	: Available
Protection against password guessing	: Available
Tampering alarm	: Available
Arm/disarm status indication	: Available
Radio signal power	: 20 mW
Communication protocol	: Jeweller (868.0-868,6 MHz)
Maximum distance between keyboard and central unit	: Up to 1,700 m (5,577 ft) (in open area)
Power supply	: 4 AAA batteries
Power supply voltage	: 3V
Battery life	: Up to 2 years
Battery charge indication	: Available
Operating temperature range	: From 0°C (+32°F) to +50°C (+122°F)
Operating humidity	: Up to 80%
Dimensions	: 150 x 122.5 x 13.2 mm
Weight	: 172 g

5

CATEGORY Smart Smoke Detector
With Temperature Sensors

FireProtect (8IN)



Classification	: Radio channel smoke detector with temperature sensor and built-in siren
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	: Photoelectric and temperature sensors
Activation threshold	: +54°C to +65°C
Type of notification	: Sound/light
Volume of built-in siren	: 85 dB
Alarm signal delivery time	: 0.15 s
False alarm filter	: +
Interconnected alarms	: +
Power supply	: Battery: Two CR2 batteries Power supply voltage: 3 V Battery life up to 4 yrs Backup battery: Cr2032
Jeweller radio technology	: Communication range with central unit — up to 1,300 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
Additional temperature sensor	: Available
Operating temperature range	: From 0°C to +65°C
Permissible humidity	: Up to 80%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: EN 14604
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

6

CATEGORY Smart Smoke Detector
With Temperature Sensors

FireProtect Plus (8IN)



Classification	: Radio channel smoke detector with temperature sensor and built-in siren
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	: Photoelectric, CO and temperature sensors
Activation threshold	: +54°C to +65°C
Type of notification	: Sound/light
Volume of built-in siren	: 85 dB
Alarm signal delivery time	: 0.15 s
False alarm filter	: +
Interconnected alarms	: +
Power supply	: Battery: Two CR2 batteries Power supply voltage: 3 V Battery life — up to 4 years Backup power supply: battery Cr2032
Jeweller radio technology	: Communication range with central unit — up to 1,300 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
Additional temperature sensor	: Available
Operating temperature range	: From 0°C to +65°C
Permissible humidity	: Up to 80%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: EN 14604
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

7

CATEGORY Intelligent
Control Panel

Ajax Hub (8IN)



Classification	: The radio channel central unit with GSM and Ethernet modules
Maximum number of devices connected to the hub	: 100
Maximum number of cameras connected to the hub	: 10
Maximum number of users	: 50
Maximum number of rooms	: 50
Maximum number of groups	: 9
Mobile applications	: iOS 9.1 and later Android 4.1 and later
Communication channels	: Ethernet, GSM (850/900/1800/1900 MHz)
Alarm signal	: Delivery time: 0.15 s Types of notifications: SMS message, call, push
Communication with Central Monitoring	: Contact ID, SIA
Processor	: ARM
Operating system	: OS Malevich
Power supply	: Mains supply: 110-240 V Battery backup: Li-Ion 2 A-h Up to 15 hours of offline operation when Ethernet is switched off Energy consumption from the grid - 10 W
Jeweller radio technology	: Communication range with detectors — up to 2,000m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s Frequency hopping
SIM card support	: Micro SIM 2G
Operating temperature range	: From -10°C to +40°C
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Video surveillance	: Up to 10 cameras or DVRs
Remote set up	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

8

CATEGORY Intelligent
Control Panel

Ajax Hub 2 (8IN)



Classification	: The radio channel central unit with the support of visual alarm verification detectors
Installation	: Indoors
Maximum amount of devices that could be connected to the hub	: 100
Video surveillance support	: Up to 25 cameras or DVRs
Maximum amount of users	: 50
Maximum amount of rooms	: 50
Maximum amount of security groups	: 9
Motion Cam detectors support	: +
Communication channels	: Ethernet two 2G SIM-cards
Alarm signals	: Delivery time: 0.15 sec Notification types: SMS, call, push-notification
Switching between the SIM-cards	: 4 minutes
CMS connectivity	: Contact ID, SIA (DC-09) Photo verification integrated in Manitou, ABSistemDC(ING), WBB, Horus, V1/F1, Kronos, eLipse, Sentinel, MASTERMind, Stages and SBN
The speed of alarm delivery to the CMS	: Instant
Software	: OS Malevich
Power supply	: Main supply: 110-240 V Battery backup: Li-Ion 2 A-h Up to 16 hours of offline operation when the Ethernet is switched off Energy consumption from the grid — 10 W
Jeweller radio technology	: Communication range with detectors — up to 2,000 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s Frequency hopping
Wings radio technology	: Transmission of visual confirmations Delivery verification of packages
Operating temperature range	: From -10°C to +40°C
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

9

CATEGORY Intelligent Control Panel

Ajax Hub 2 Plus (8IN)



Classification	: Security system control panel with four in-built channels for external communication and support of detectors with photo cameras
Connected devices	: 200
Video surveillance support	: 100 cameras and DVRs
Users	: 200
Rooms	: 50
Security groups	: 25
Connected ReX	: 5
Scenarios	: 64
MotionCam detectors support	: +
Apps	: iOS 11.0 and later Android 4.4 and later
Communication channels	: 2 SIM cards 2G (GSM900/DCS1800 (B3/B8)) 3G (WCDMA 850/900/2100 (B1/B5/B8)) LTE (FDD B1/B3/B5/B7/B8/B20) Wi-Fi (802.11 b/g/n) Ethernet Delivery time: 0.15 sec Notification types: SMS, call, push-notification
Alarm signals	: Instant
Switching between 2G, 3G, LTE	: 4 minutes
Switching between the SIM-cards	: Contact ID, SIA (DC-09) Photo verification integrated in Manitou, ABsistemDC(NG), WBB, Horus, V1/F1, Kronos, eLipse, Sentinel, MAMsterMind, Stages and SBN
CMS connectivity	: OS Malevich
Operating system	: 110–240 V from mains Built-in back-up battery: Li-Ion 3 Ah Up to 15 hours of autonomous work when Ethernet or Wi-Fi channels are disabled Energy consumption from mains- 10 W
Power supply	: Communication range with detectors — up to 2,000 m in an open space
Jeweller radio technology	: Two-way communication between devices Operating frequencies — 865–867 Mhz
Wings radio technology	: Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12–300 s Frequency hopping
	: Transmission of visual confirmations Delivery verification of packages
Operating temperature range	: From -10°C to +40°C
Anti-sabotage	: Forgery prevention Notifications about jamming Tamper to detect back lid opening and unmounting from SmartBracket
Remote set up and testing	: +
Certification	: DSTU EN 50131
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

10

CATEGORY Flood Detector

LeaksProtect (8IN)



Classification	: Radio channel water leak
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Alarm signal delivery time	: 0,15 s
Power supply	: Battery: Two AAA batteries Power supply voltage: 3 V Battery life — up to 5 years
Jeweller radio technology	: Communication range with central unit — up to 1,300 m in an open space Two-way communication between devices Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12–300 s
Temperature sensor	: Available
Operating temperature range	: 0°C to +50°C
Permissible humidity	: Up to 100%
Protection class	: IP65
Anti-sabotage	: Protection against fraud Jamming detection
Remote setting and testing	: +
Certification	: CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

11

CATEGORY The Smallest Acoustic Glass Break Detector

GlassProtect (8IN)



Classification	: Surface sound radio channel security detector
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	: Electret microphone
Break detection distance	: Up to 9 m
Alarm signal delivery time	: 0,15 s
Sensitivity	: Adjustable, 3 levels
Detection angle	: 180°
Power supply	: Battery: CR123A battery Power supply voltage: 3 V Battery life — up to 7 years
Jeweller radio technology	: Communication range with central unit — up to 1,000 m in an open space Two-way communication between devices Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12–300 s
Temperature sensor	: Available
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

12

CATEGORY Wireless Indoor Siren

HomeSiren (8IN)



Classification	: Radio channel security sounder
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates only with Hub, Hub Plus and ReX
Type of notification	: Sound
Connector for external LED	: Available
Sound volume level	: Adjustable, 81–105 dB at a distance of 1 m
Alarm length	: Adjustable, 3–180 s
Indication of armed/disarmed status	: Yes
Alarm signal delivery time	: 0,15 s
Power supply	: Battery: Two CR123A batteries Power supply voltage: 3V Battery life — up to 5 Yrs
Jeweller radio technology	: Communication range with central unit — up to 2,000 m in an open space Two-way communication between devices Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12–300 s
Temperature sensor	: Available
Operating temperature range	: -10°C to +40°C
Permissible humidity	: Up to 75%
Protection class of body	: Ip50
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

13

CATEGORY Pet Immune Motion PIR
Detector Microwave Sensor

MotionProtect



Classification	: Electro-optical combined radio channel security detector
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates with all Ajax hubs, range extenders, ocBridge Plus, uartBridge
Sensing element	: PIR sensor, microwave sensor (24 GHz)
Alarm signal delivery time	: 0.15 s
Motion detection distance	: Up to 12 m
Detection angles	: Horizontal — 88.5° Vertical — 80°
Sensitivity	: Adjustable, 3 levels
Recommended installation height	: 2.4 m
Pet immunity	: Weight — up to 20 kg Height — up to 50 cm
Power supply	: Battery: CR123A battery Power supply voltage: 3 V Battery life — up to 5 years
Jeweller radio technology	: Communication range with central unit — up to 1,700 m in an open space
Temperature sensor	: Two-way communication between devices Operating frequencies — 865—867 Mhz
Operating temperature range	: Self-adjusting RF output power — limit 20 mW Block encryption based on AES
Permissible humidity	: algorithm Device polling period — 12–300 s
Anti-sabotage	: Available
Remote setting and testing	: From -10°C to +40°C
Dimensions	: Up to 75%
Weight	: Protection against fraud Jamming detection Tamper-resistant
Certification	: +
Warranty	: Grade 2, CE Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

14

CATEGORY Pet Immune Motion PIR
Detector Microwave Sensor

MotionProtect Plus (8IN)



Classification	: Electro-optical combined radio channel security detector
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Operates with all Ajax hubs, range extenders, ocBridge Plus, uartBridge
Sensing element	: PIR sensor
Alarm signal delivery time	: 0.15 s
Motion detection distance	: Up to 12 m
Detection angles	: Horizontal — 88.5° Vertical — 80°
Sensitivity	: Adjustable, 3 levels
Recommended installation height	: 2.4 m
Pet immunity	: Weight — up to 20 kg Height — up to 50 cm
Power supply	: Battery: CR123A battery Power supply voltage: 3 V Battery life — up to 5 years
Jeweller radio technology	: Communication range with central unit — up to 1,700 m in an open space
Temperature sensor	: Two-way communication between devices Operating frequencies — 865—867 Mhz
Operating temperature range	: Self-adjusting RF output power — limit 20 mW Block encryption based on AES
Permissible humidity	: algorithm Device polling period — 12–300 s
Anti-sabotage	: Available
Remote setting and testing	: From -10°C to +40°C
Dimensions	: Up to 75%
Weight	: Protection against fraud Jamming detection Tamper-resistant
Certification	: +
Warranty	: Grade 2, CE Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

15

CATEGORY Pet Immune
Motion PIR Detector

MotionCam (8IN)



Classification	: Electro-optical combined radio channel security detector with a photo camera
Detector type	: Wireless
Installation	: Indoors
Motion detection distance	: Up to 12 m
Pet immunity	: Weight: up to 20 kg Height: up to 50 cm
Compatibility	: Only with Hub 2, Hub 2 Plus
Sensing element	: PIR-sensor
Alarm signal delivery time	: 0.15 sec
Detection angles	: Horizontal — 88.5° Vertical — 80°
Camera view angle	: 90°
Photo verification	: Time to deliver a photograph with default settings: up to 9 sec Photo quality: up to 640 × 480 Pictures in a series: 1–5 pcs
IR-backlight for night mode pictures	: Available
Sensitivity	: Adjustable, 3 levels
Recommended installation height	: 2.4 m
Power supply	: Batteries: CR123A (x2) Power supply voltage: 3 V Battery life: up to 4 years (up to 2.5 years if "Delay when entering" setting is activated)
Jeweller radio technology	: Communication range with detectors: up to 1,700 m in the line of sight Two-way communication between devices Operating frequencies: 865–867 Mhz Self-adjusting RF output power: limit 20 mW Block encryption based on AES algorithm Detector polling period: 12–300 s Frequency hopping
Wings radio technology	: Transmission of visual alarm verifications
Temperature sensor	: Available
Operating temperature range	: From 0°C to +40°C (manufacture date up to June 1, 2020) From -10°C to +40°C (manufacture date from June 1, 2020)
Operating humidity	: Up to 75%
Anti-sabotage	: Fraud protection Jamming notification Tamper-resistant
CMS compatibility	: Motion alarms are transmitted to CMSs that support SIA (DC-09) and Contact ID protocols.
Remote configuration and testing	: Visual alarm verifications are transmitted to the Manitou, Absistem DC(NQ,WBB, Horus, V1/F1, Kronos, eLipse, Sentinel, MASter Mind, Stages and SBN CMS, and Ajax PRO Desktop app
Protection class	: +
Certification	: Ip50
Warranty	: Security Grade 2, Environmental Class II in conformity with the requirements of EN 50131 Replacement and repair for a period of 24 months from the date of sale. The warranty does not cover batteries.

16

CATEGORY Pet Immune
Motion PIR Detector

MotionProtect Outdoor (8IN)




Classification	: Electro-optical radio channel security detector
Type of detector	: Wireless
Installation method	: Outdoors/indoors
Compatibility	: Operates only with Hub, Hub Plus and ReX
Sensing element	: Two PIR sensors
Alarm signal delivery time	: 0.15 seconds
Motion detection distance	: Adjustable, up to 3—15 m
Detection angles	: Horizontally—90°
Sensitivity	: Adjustable, 3 levels
Recommended installation height	: 0.8—1.3 m
Pet-immunity	: Weight — not relevant Height — up to 80 cm
Power supply	: Power supply: 2 × CR123A battery Power supply voltage: 3 V Battery life — up to 5 years Mains supply: DC 12 V±20%
Jeweller radio technology	: Communication range with central unit — up to 1,700 m in an open space
Temperature sensor	: Two-way communication between devices Operating frequencies — 865–867 Mhz
Operating temperature range	: Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm
Operating humidity	: Detector polling period — 12–300 s
Protection class	: Available
Anti-sabotage	: From -25°C to +60°C
Remote configuration and testing	: Up to 95%
Certification	: Ip55
Warranty	: + Anti-masking Protection against fraud Jamming detection Tamper-resistant
	: +
	: Conforms to the requirements of CU TR 020/2011 «Electromagnetic compatibility of technical means», EAC
	: DSTU EN 50131
	: Replacement and repair for a period of 24 months from the date of sale. The warranty does not cover batteries.

MotionProtect Curtain (8IN)



Technical specifications	: Radio-interlinked photoelectric security detector
Classification	: Wireless
Type of detector	: Indoors only
Installation	: Operates with all Ajax hubs, and range extenders
Compatibility	: Two PIR sensors
Sensing element	: 0.15 seconds
Alarm signal delivery time	: Up to 15 m
Motion detection distance	: Horizontally—6°
Detection angles	: Vertically—90°
Sensitivity	: Adjustable, 3 levels
Recommended installation height	: 2.4 meters
Power supply	: Battery: CR123A Power supply voltage 3 V Battery life: up to 3 years
Jeweller radio technology	: Communication range with detectors — up to 1,700 m in an open space
	: Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s
	Frequency hopping
	Available
Temperature sensor	: From -10°C to +40°C
Operating temperature range	: Up to 95%
Operating humidity	: Fraud protection Jamming notification Tamper-resistant
Anti-sabotage	: +
Remote configuration and testing	: Ip54
Protection class	: Replacement and repair for a period of 24 months from the date of sale. The warranty does not cover batteries. MotionProtect Curtain motion detector
Warranty	

uartBridge(8IN)



Classification	: Receiver of wireless detectors' signal
Type of detector	: Wireless
Installation method	: Indoors
Compatibility	: Wired security systems and smart home systems
Maximum number of detectors	: 85
Supported devices	: MotionProtect MotionProtect Plus CombiProtect DoorProtect
	: FireProtect FireProtect Plus LeaksProtect SpaceControl
	: GlassProtect
Alarm signal delivery time	: 0.15 s
Power supply voltage	: 5V DC
Jeweller radio technology	: Communication range with detectors — up to 2,000m in an open space
	Two-way communication with detectors
	Operating frequencies — 865-867MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Operating temperature range	: -10°C to +40°C
Permissible humidity	: Up to 90%
Anti-sabotage	: Protection against fraud Jamming detection
Interface	: UART
Certification	: CE
Warranty	: Replacement and repair within 24 months of the date of sale.

Wireless Remote Control Relay | WallSwitch(8IN)



Classification	: Radio channel relay unit
Device type	: Wireless
Installation method	: Into wall plate
Compatibility	: Operates only with hub Ajax and ReX
Actuating element	: Relay
Relay service life	: 200,000 switch-ons
Voltage protection	: For 230 V mains: max — 264 V, min — 161 V For 110V mains: max — 126 V, min — 77 -13A
	: Yes (13A)
Maximum load current	: >65°C in the wall plate
Maximum current protection	: Resistive load at 230 V— up to 3 kW Resistive load at 110V— up to 1.5 kW
Maximum temperature protection	: Available
Permissible power	: Current, voltage, power consumption
Electric power meter function	: 0.15 s
Energy consumption parameter check	: 110-230 V±10% 50/60 Hz
Alarm signal delivery time	: Impulse (firmware version 5.54.1.0 or higher) Bistable
Power supply	: Normally open Normally closed
Operation modes	: 0.5 - 255 sec
Contact state (firmware version 5.54.1.0 or higher)	: Communication range with central unit — up to 1,000 m in an open space
Adjustable pulse duration (firmware version 5.54.1.0 or higher)	: Two-way communication between devices Operating frequencies — 865-867 Mhz
Jeweller radio technology	: Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm
Operating temperature range	: Detector scanning period — 12-300 s
Permissible humidity	: 0°C to +64°C
Protection class of body	: Up to 75%
Anti-sabotage	: Ip20
Remote setting and testing	: Protection against fraud Jamming detection
Certification	: +
Warranty	: CE
	: Replacement and repair within 24 months of the date of sale.

Ajax ReX (8IN)




Classification	: Radio channel range extender
Device type	: Wireless
Installation method	: Indoors
Compatibility	: Hub and Hub Plus featuring OS Malevich 2.7.1 and later
Alarm signal delivery time	: 0.3 seconds
Maximum connected devices	: Hub — up to 99 Hub Plus — up to 149
Max number of connected ReX per hub	: 1
Operating system	: OS Malevich
Power supply	: Mains supply: 110-240 V Battery backup: Li-Ion 2 A h Up to 35 hours of offline operation
Jeweller radio technology	: Communication range with detectors — up to 1,800 m in an open space Two-way communication between devices Operating frequencies — 865-867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector polling period — 12-300 s Frequency hopping
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Warranty	: Within 24 months from the date of sale

MultiTransmitter (8IN)



Number of alarm/tamper zones	: 18
Supported detector contact types	: NO, NC (without R), EOL (NC with R), EOL (NO with R)
Resistance of the EOL resistor	: 1 kΩ to 7.5 kΩ
Alarm signals processing mode	: Pulsed or bistable
Main power supply	: 110–255 V, 50/60 Hz
Backup power	: 12 V DC
Supported battery type	: Battery with 4 or 7 A · h capacity (not included)
Detector power supply	: 12 V DC, up to 1 A for all detector power supply outputs
Protection against dismantling	: Tamper
Radio signal frequency band	: 865–867 Mhz
Compatibility	: Operates with Hub, Hub Plus, Hub 2, Hub 2 Plus and ReX
Maximum radio signal power	: limit 20 mW
Radio signal range	: Up to 2,000 m in the line of sight
Operating temperature range	: From -10°C to +40°C
Operating humidity	: Up to 75%
Warranty	: Replacement and repair for a period of 24 months from the date of sale.

ocBridge Plus (8IN)



Classification	: Receiver of wireless detectors
Installation method	: Indoors
Compatibility	: Wired and hybrid security systems
Number of security areas	: 8
Number of service areas	: 4
Loops	: NO/NC, EOL, 2EOL
Maximum number of detectors	: 99
Supported devices	: MotionProtect MotionProtect Plus Combiprotect DoorProtect FireProtect FireProtect Plus LeaksProtect SpaceControl GlassProtect
Alarm signal delivery time	: 0.15 s
Power supply	: Terminals +/ground
Power supply voltage	: 8–14 V DC miniUSB — 5 V (only for set up)
Jeweller radio technology	: Communication range with detectors — up to 2,000 m in an open space Two-way communication with detectors Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period 12–300 s
Capability of external antenna connection	: Yes
Software update feature	: Yes
Operating temperature range	: -10°C to +40°C
Permissible humidity	: Up to 90%
Anti-sabotage	: Protection against fraud Jamming detection Tamper
Setting up and testing	: Via configurator for PC
Interface	: miniUSB
Warranty	: CE : Replacement and repair within 24 months of the date of sale.

Ajax Relay (8IN)



Classification	: Radio channel relay unit
Device type	: Wireless
Installation method	: Into electric switchboard, junction box
Compatibility	: Operates only with hub Ajax and ReX
Actuating element	: Electromagnetic relay
Relay service life	: 200,000 switch-ons
Voltage protection	: Max — 36.5 V, min — 6.5 V
Maximum load current	: 5A at 36V DC, 13A at 230V AC
Maximum current protection	: No
Maximum temperature protection	: 65°C at the place of installation
Electric power meter function	: No
Energy consumption parameter check	: Voltage
Alarm signal delivery time	: 0.15 s
Power supply	: 7–24 V (DC only)
Operation modes	: Impulse Bistable
Contact state	: Normally open Normally closed
Adjustable pulse duration	: 0.5 – 255 sec
Jeweller radio technology	: Communication range with central unit — up to 1,000 m in an open space Two-way communication between devices Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device scanning period — 12–300 s
Operating temperature range	: 0°C to +64°C
Permissible humidity	: Up to 75%
Protection class of body	: Ip20
Anti-sabotage	: Protection against fraud Jamming detection
Remote setting and testing	: +
Certification	: CE
Warranty	: Replacement and repair within 24 months of the date of sale.

Ajax Button (8IN)



Classification	: Addressed Radio Panic Button
Compatibility	: Operates with hub Ajax, and ReX featuring OS Malevich 2.7.102 and later
False alarm prevention	: Yes (in the Panic mode)
Number of buttons	: 1
Alarm transmission	: Not longer than 0.15 sec Active from the first click (no need to wake it up)
Adjustable alarm types	: Intrusion Fire Medical help Panic button Gas
Jeweller radio technology	: Communication range with a hub — up to 1300 m in an open area Two-way communication channel Operating frequencies — 865–867 Mhz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Frequency hopping
Power supply	: Battery: CR2032 battery Power supply voltage: 3 V Battery life — up to 5 years
Operating temperature range	: From -10°C to +40°C
Permissible humidity	: Up to 75%
Protection class	: Ip55
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

21

CATEGORY

Key Fob With a
Panic Button

SpaceControl(8IN)



Classification	: Four-button key for with command delivery indication
Compatibility	: Operates with all Ajax hubs, and range extenders, ocBridge Plus, uartBridge
Number of buttons	: 4
False alarm prevention	: Yes, long press or double press (firmware version 5.54.1.0 or higher. Manufacture date from March 19, 2020)
Deactivation of the panic button	: Available
Power supply	: Battery: CR2032 battery
Jeweller radio technology	: Power supply voltage: 3V Battery life — up to 5 years : Communication range with central unit — up to 1,300 min an open space Two-way communication between devices Operating frequencies — 865-867 MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Operating temperature range	: -25°C to +50°C
Permissible humidity	: Up to 95%
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale.

22

CATEGORY

Wireless
Street Siren

StreetSiren(8IN)



Classification	: Light and sound radio channel security sounder
Type of detector	: Wireless
Installation method	: Indoors/outdoors
Compatibility	: Operates only with Hub, Hub Plus and ReX
Type of notification	: Sound/light
Sound volume level	: Adjustable, 81-113 dB at a distance of 1m
Alarm length	: Adjustable, 3-180 s
Indication of armed/disarmed	: Yes
Alarm signal delivery time	: 0.15 s
Power supply	: Battery: Four CR123A batteries Power supply voltage: 3V Battery life — up to 5 years Mains supply: DC 12 V ±20%
Jeweller radio technology	: Communication range with central unit — up to 1,500 min an open space Two-way communication between devices Operating frequencies — 865-867 MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: -25°C to +50°C
Permissible humidity	: Up to 95%
Protection class of body	: Ip54
Anti-sabotage	: Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	: +
Certification	: Grade 2, CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

23

CATEGORY

Wireless
Street Siren

StreetSiren Double Deck(8IN)



Classification	: Warning device with LED indicators (outdoor siren)
Type of siren	: Wireless
Installation method	: Outdoors/indoors
Compatibility	: Operates only with Hub, Hub Plus, Hub 2, Hub 2Plus and ReX
Type of notification	: Sound/light
Sound volume level	: Adjustable, 85-113 dB at a distance of 1m
Alarm duration	: Adjustable, 3-180 s
Indication of armed/disarmed	: Available
Power supply	: Battery: Four CR123A batteries, 3V Mains supply: DC 12 V ±20%
Battery life	: Up to 5 years Learn more
Jeweller radio technology	: Communication range with central unit — up to 1,500 min an open space : Two-way communication between devices Operating frequencies — 865-867 MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: From -25°C to +60°C
Permissible humidity	: Up to 95%
Ingress protection rating	: IP54
Anti-sabotage	: Forgery prevention Jamming detection Tamper-resistant
Remote configuring and testing	: Available
Certification	: DSTU EN 50131, In compliance with the requirements of the technical regulations governing radio equipment
Color	: White/Black
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

24

CATEGORY

Transmitter (8IN)



Classification	: Module for third-party detector integration
Device type	: Wireless
Installation method	: Indoors/outdoors
Compatibility	: Operates only with hub Ajax and ReX
Alarm input	: 1
Tamper input	: 1
Power supply current	: Terminals +/-
Power supply output	: 3.3V
Battery charge indication	: Yes
Adjustable alarm types	: Intrusion Fire Medical help Panic button as
Alarm signal delivery time	: 0.15 s
Power supply	: Battery : Three CR123A batteries Power supply voltage: 3V Battery life — up to 5 years
Jeweller radio technology	: Communication range with central unit — up to 1,600 min an open space : Two-way communication between devices Operating frequencies — 865-867 MHz Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	: Available
Operating temperature range	: -25°C to +50°C
Permissible humidity	: Up to 75%
Anti-sabotage	: Protection against fraud Jamming detection Accelerometer to detect removal
Remote setting and testing	: +
Certification	: CE
Warranty	: Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.

29

CATEGORY

Ajax StarterKit (8IN)



The kit includes:

HUBKIT

- Hub - Intelligent control panel
- Motion Protect - Motion detector
- Door Protect - Opening detector
- Space Control - key fob

30

CATEGORY

Ajax StarterKit Cam (8IN)



The kit includes:

HUBKIT 2.0

- Hub - Intelligent control panel
- Motion Protect - Motion detector
- Door Protect - Opening detector
- Space Control - key fob

31

CATEGORY

Ajax StarterKit Cam Plus (8IN)



The kit includes:

HUBKIT 2.0 Plus

- Hub 2 Plus - Intelligent control panel supporting Visual alarm
- Motion Cam - Motion detector with Visual alarm
Color: Black/White
- Door Protect - Opening detector
- Space Control - key fob
- Distance between keyfob & Hub: Up to 1,300m in open are

32

CATEGORY

Ajax Socket (8IN)



Classification
Device type
Installation method
Compatibility
Actuating element
Voltage and type of external power supply
Voltage protection for 230 V mains
Relay service life
Maximum load current
Maximum current protection
Maximum temperature protection
Electric shock protection class
Electric power meter feature
Energy consumption parameter check
Alarm signal delivery time
Load indicator
Output power (resistive load at 230 V)
Average energy consumption of the device on standby
Operation modes
Contact state (firmware version 5.54.1.0 or higher)
LED indication
Adjustable pulse duration (firmware version 5.54.1.0 or higher)
Jeweller radio technology

Operating temperature range
Permissible humidity
Protection class of body
Anti-sabotage
Remote setting and testing
Warranty

Radio channel relay unit
Wireless
In power outlet
Operates only with hub Ajax and ReX
Electromagnetic relay
110 - 230 V, 50/60 Hz
Yes, 184-253 V
200,000 switch-ons
11 A (continuous), 13 A (up to 5 s)
Yes, 11 A if the protection is turned on, up to 13 A if the protection is turned off
Yes, +85°C. The socket turns off automatically if the temperature is exceeded
Class I (with grounding terminal)
Available
Current, voltage, power consumption
0.15 s
Available
Up to 2.5 kW
Less than 1 W
Impulse (firmware version 5.54.1.0 or higher) Bistable
Normally open Normally closed
Adjustable
0.5 - 255 sec
Communication range with central unit — up to 1,000 m in an open space
Two-way communication between devices Operating frequencies — 865-867 Mhz
Self-adjusting RF output power — limit 20 mW Block encryption based on AES algorithm Detector
scanning period — 12-300 s
0°C to +40°C
Up to 75%
IP20
Protection against fraud Jamming detection
Replacement and repair within 24 months of the date of sale.



The Ajax Security System app is a virtual control center, available day and night. You can check the system status, arm/disarm it or change the system configuration. All with just a few taps on your smartphone or computer.



Arming/
disarming



Instant
notifications




Detailed info
about device
status



Remote
testing and
configuration



Regular
updates



We created a digital ecosystem that increases the capabilities of Ajax devices. Thanks to Ajax Cloud, all processes are regulated and accurate. It takes just milliseconds to send an alarm from the hub to the server and then to the user. The system can be configured remotely with a few clicks. And every remote firmware update increases the functionality of the system.

Specs

- Hub polling every 10 seconds
- Detailed info about device status
- Remote system setup
- Automatic software updates
- Direct connection with CMS